ANNEX A TO DGDP TENDER NO 214.1531.24 DATED: 28 NOVEMBER 2024

LIST OF OF BATTERY VARIOUS SIZES FOR DIFFERENT VEH, QTY-06 LINE ITEMS

Ser	Cat/Part No	Nomenclature	A/U	Applicability	Qty	Rmks
1.	5801985805	Bty 12 Volt 180 AH 23 Plate 1000 A (EN) L: 500 mm W: 220 mm H: 235 mm	Nos	Truck Recovery Greater Than 5 Ton ASTRA Model: HD9 66.42 (Wrecker TEKNE 200)	40	
2.	35298/6140- 057-2553	Bty 12 Volt 45 AH 13 Plate L: 235 mm W: 132 mm(Top) H: 220-230 mm	Nos	Nissan N-16, Mitsubishi CS-3, CK-1	100	
3.	NIV-180133	Bty 12 Volt 75 AH L: 305 mm W: 167 mm H: 208 mm	Nos	TATA HEXA XT	70	
4.	26-14-4	Bty 12 Volt 155 AH 23 Plate (With wooden box) L: 510-540 mm W: 177-240 mm H: 230-238 mm	Nos	Tank T-59, T-69 & ARV T-84	100	
5.	35300	Bty 12 Volt 65 AH 13 Plate L: 258-260 mm W: 170-173 mm H: 221-230 mm	Nos	Trk 3 Ton Isuzu- HTS11G & 11J, Toyota HZJ-71 & 79	200	
6.	28800-54140	Bty 12 Volt 65 AH 13 Plate L : 260 mm W: 173 mm H: 225 mm	Nos	Toyota Coaster BB-21 RMR, Isuzu Trk 3 Ton HTS-11J	50	
(Tota	al ItemsSix Onl	у)		Total Items/Qty= 0	6 / 560N	os

A 1 of 1 FOR OFFICIAL USE ONLY



ANNEX B TO DGDP TENDER NO 214.1531.24 DATED: 28 NOVEMBER 2024

ITEM NO. 1, TECHNICAL SPECIFICATION OF SECONDARY BATTERY 12 VOLT 180 AH 23 PLATE1000 A(EN), QTY-40 NOS

Ser	G	eneral Description	Technical Specification	Must be filled up by the Manufacturer
Part -	<u>.1</u>			
	Ger	neral Specification		
1.	Nomenclature		Secondary Battery 12 Volt 180 AH 23 Plate 1000 A(EN)	
2.	Brand & Model		(LUCAS, HAMKO, GENERAL, NAVANA, VOLVO, RANGS POWER, RIMSO and SAIF POWER). Specific Brand to be mentioned	
3.	Nar	ne of manufacturer	To be mentioned	
	with	complete address		
4.	Cou	intry of Origin	To be mentioned	
5.	Cou	intry of Manufacturer	To be mentioned	
6.	Cou	intry of Assembly	To be mentioned	
7.	Yea	r of production	Not before the calendar year of	
		-	contract	
8.	Applicability		Truck Recovery Greater Than 5 Ton ASTRA Model: HD9 66.42 (Wrecker TEKNE 200)	
Part -	-2		(4445-3461-1-24-4)	
		AL SPECIFICATION		
9.		oction & Capability	Details to be mentioned	
10.		erall weight of battery	To be mentioned	
10.		PP container	10 be memoried	
11.		tery 12 Volt180 AH	To be provided	
'''	—	Voltage	12V	
	b.	Capacity`	180 AH (Min)	
	c.	No. of Plate	23 Plate	
	d.	Dimension	L = 500 mm	
	۱ ۳۰	Billionololi	W=220 mm	
			H= 235 mm	
12.	. After discharging the minimum specific gravity at 30°C of the electrolyte.		1.050-1.100	
13.	Dis	charge Rate	C/20	
14.	Cel	l Capacity	Minimum 2.1 Volts	
15.	Sep	parators	To be mentioned	neral of Dos
			B 1 of 12	1/2

B 1 of 12 FOR OFFICIAL USE ONLY

nistry of Dele

Ser	Gene	ral Description	Technical Specification	Must be filled up by
16.	Contain	er	White Plastic Container with carrying handle/rope and screen print instrument. Upper and lower level of electrolyte identification mark should be leveled on the body of the battery	the Manufacturer
17.	Self dis	charge rate	3% ~ 4% per month	
18.	Warranty		Minimum 01(One) year from the date of actual use (After filling the electrolyte).	
19.	Per Battery Electrolyte Capacity including container		To be mentioned	
20.	Density of Electrolyte at 20°C		To be mentioned	
21.	Physical AppearanceofShulphuric acid		Clear, colorless, odorless liquid	
22.	Shulph	uric acid		
	a. Pu	ırity	99.97%	
	b. De	ensity at 20°C	1.84	
23.	DM wa	ter (P ^H value)	PH= 5-6	
24.	<u>Plate</u>			
	a. No	of positive plate	To be mentioned	
	b. No	o of Negative ate	To be mentioned	

B 2 of 12 FOR OFFICIAL USE ONLY



ITEM NO. 2, TECHNICAL SPECIFICATION OF SECONDARY BATTERY 12 VOLT 45 AH 13 PLATE, QTY-100 NOS

Ser	Ge	eneral Description	Technical Specification	Must be filled up by the Manufacturer
Part -	1			
	Ger	eral Specification		_
1.	Nomenclature		Secondary Battery 12 Volt 45 AH 13 Plate	
2.	Brand & Model		(LUCAS, HAMKO, GENERAL, NAVANA, VOLVO, RANGS POWER, RIMSO and SAIF POWER). Specific Brand to be mentioned	
3.		ne of manufacturer complete address	To be mentioned	
4.	Cou	ıntry of Origin	To be mentioned	
5.	Cou	intry of Manufacturer	To be mentioned	
6.	Cou	intry of Assembly	To be mentioned	
7.	Yea	r of production	Not before the calendar year of contract	
8.	App	licability	Nissan N-16, Mitsubishi CS-3, CK-1	
Part ·	<u>-2</u>			
TECH	INIC	AL SPECIFICATION		
9.	Fun	ction & Capability	Details to be mentioned	
10.	Overall weight of battery with PP container		To be mentioned	
11.	Bat	tery 12 Volt 45 AH	To be provided	
	a.	Voltage	12V	
	b.	Capacity`	45 AH (Min)	
	c.	No. of Plate	13 Plate	
	d.	Dimension	L = 235 mm	
			W=132 mm(Top)	
			H= 220-230 mm	
12.	After discharging the minimum specific gravity at 30°C of the electrolyte.		1.050-1.100	
13.	Dis	charge Rate	C/20	
14.	Cell Capacity		Minimum 2.1 Volts	
15.	Separators		To be mentioned	
16.	Cor	ntainer	White Plastic Container with carrying handle/rope and screen print instrument. Upper and lower level of electrolyte identification mark should be leveled on the body of the battery	araloto

B 3 of 12 FOR OFFICIAL USE ONLY

Ser	General Description	Technical Specification	Must be filled up by the Manufacturer
17.	Self discharge rate	3% ~ 4% per month	
18.	Warranty	Minimum 01(One) year from the date of actual use (After filling the electrolyte).	
19.	Per Battery Electrolyte Capacity including container	To be mentioned	
20.	Density of Electrolyte at 20°C	To be mentioned	
21.	Physical Appearance of Shulphuric acid	Clear, colorless, odorless liquid	
22.	Shulphuric acid		
	a. Purity	99.97%	
	b. Density at 20°C	1.84	
23.	DM water (PH value)	P ^H = 5-6	
24.	<u>Plate</u>		
	a. No of positive plate	To be mentioned	•
	b. No of Negative Plate	To be mentioned	



ITEM NO.3, TECHNICAL SPECIFICATION OF SECONDARYBATTERY 12 VOLT 75 AH, QTY-70 NOS

Ser	Ge	eneral Description	Technical Specification	Must be filled up by the Manufacturer
Part -	1			
-	Gen	eral Specification		
1.	Nomenclature		Secondary Battery 12 Volt 75 AH	
2.			(LUCAS, HAMKO, GENERAL, NAVANA, VOLVO, RANGS POWER, RIMSO and SAIF POWER). Specific Brand to be mentioned	
3.		ne of manufacturer complete address	To be mentioned	
4.	Cou	intry of Origin	To be mentioned	
5.	Cou	intry of Manufacturer	To be mentioned	
6.	Cou	intry of Assembly	To be mentioned	
7.	Yea	r of production	Not before the calendar year of contract	
8.	App	licability	TATA HEXA XT	
Part_	<u>-2</u>			
TECH	<u>INIC/</u>	AL SPECIFICATION		
9.	Fun	ction & Capability	Details to be mentioned	
10.		erall weight of battery PP container	To be mentioned	
11.	Bat	tery 12 Volt75 AH	To be provided	
	a.	Voltage	12V	
	b.	Capacity`	75 AH (Min)	
	C.	No. of Plate	To be mentioned	
	d.	Dimension	L=305 mm	
			W=167 mm	
			H= 208 mm	
12.		er discharging the nimum specific gravity 80°C of the electrolyte.	1.050-1.100	
13.	Dis	charge Rate	C/20	
14.	Cel	l Capacity	Minimum 2.1 Volts	
15.	Separators		To be mentioned	
16.	Cor	ntainer	White Plastic Container with carrying handle/rope and screen print instrument. Upper and lower level of electrolyte identification mark should be leveled on the body of the battery	

B 5 of 12 FOR OFFICIAL USE ONLY

Ser	G	eneral Descr	ription	Technical Specification	Must be filled up by the Manufacturer
17.	Self	discharge rat	te	3% ~ 4% per month	
18.	War	ranty		Minimum 01(One) year from the date of actual use (After filling the electrolyte).	
19.		Battery El acityincluding tainer	lectrolyte g	To be mentioned	
20.	Density of Electrolyte at 20°C		rolyte at	To be mentioned	
21.	Physical			Clear, colorless, odorless liquid	
	App	earanceofSh	ulphuric		
	acio				
22.	<u>Sh</u>	<u>ılphuric acid</u>	<u>i</u>		
	a.	Purity		99.97%	
	b.	Density at 2	20°C	1.84	
23.	DM	water (PH va	ılue)	P ^H = 5-6	
24.	<u>Plate</u>		,		
	a.	No of positive	ve plate	To be mentioned	
	b.	No of I	Negative	To be mentioned	



ITEM NO. 4, TECHNICAL SPECIFICATION OF SECONDARY BATTERY 12 VOLT 155 AH 23 PLATE (WITH WOODEN BOX), QTY-100 NOS

Ser	(General Description	Technical Specification	Must be filled up by the Manufacturer
Part -	1			
	Gen	eral Specification		
1.	Non	nenclature	Secondary Battery 12 Volt 155 AH 23 Plate(With wooden box)	
2.	Brand & Model		(LUCAS, HAMKO, GENERAL, NAVANA, VOLVO, RANGS POWER, RIMSO and SAIF POWER). Specific Brand to be mentioned	
3.	1	ne of manufacturer with plete address	To be mentioned	
4.	Cou	intry of Origin	To be mentioned	
5.	Cou	intry of Manufacturer	To be mentioned	
6.	Cou	intry of Assembly	To be mentioned	
7.	Yea	r of production	Not before the calendar year of contract	
8.	Applicability		Tank T-59, T-69 & ARV T-84	
Part -	<u>-2</u>			1
TECH	HNICA	AL SPECIFICATION		
9.	Fun	ction & Capability	Details to be mentioned	
10.	Overall weight of battery with PP container		To be mentioned	
11.	Bat	tery 12 Volt 155 AH	To be provided	
	a.	Voltage	12V	
	b.	Capacity`	155 AH (Min)	
	C.	No. of Plate	23 Plate	
	d.	Dimension	L=510-540 mm	
			W=177-240 mm	
			H= 230-238 mm	
12.	After discharging the minimum specific gravity at 30°C of the electrolyte.		1.050-1.100	
13.	Dis	charge Rate	C/20	
14.	Cel	l Capacity	Minimum 2.1 Volts	
15.	Separators		To be mentioned	
16.	Cor	ntainer	White Plastic Container with carrying handle/rope and screen print instrument. Upper and lower level of electrolyte identification mark should be leveled on the body of the battery	neral of Dec

B 7 of 12 FOR OFFICIAL USE ONLY

Ser	General Description	Technical Specification	Must be filled up by the Manufacturer
17.	Self discharge rate	3% ~ 4% per month	
18.	Warranty	Minimum 01(One) year from the	
		date of actual use (After filling the	
<u> </u>		electrolyte).	
19.	Per Battery Electrolyte	To be mentioned	
	Capacity including		
	container		
20.	Density of Electrolyte at	To be mentioned	
	20°C		
21.	Physical Appearance of	Clear, colorless, odorless liquid	
	Shulphuric acid		
22.	Shulphuric acid		
	a. Purity	99.97%	
	b. Density at 20°C	1.84	
23.	DM water (P ^H value)	P ^H = 5-6	
24.	<u>Plate</u>		
	a. No of positive plate	To be mentioned	
	b. No of Negative Plate	To be mentioned	

DODP Inthate

ITEM NO. 5, TECHNICAL SPECIFICATION OF SECONDARY BATTERY 12 VOLT 65 AH 13 PLATE, QTY-200 NOS

Ser	Ge	eneral Description	Technical Specification	Must be filled up by the Manufacturer
Part -	1			
	Ger	eral Specification		
1.	Nomenclature		Secondary Battery 12 Volt 65 AH	
			13 Plate	
2.	Brai	nd & Model	(LUCAS, HAMKO, GENERAL, NAVANA, VOLVO, RANGS POWER, RIMSO and SAIF POWER). Specific Brand to be mentioned	
3.		ne of manufacturer complete address	To be mentioned	
4.	Cou	intry of Origin	To be mentioned	
5.	Cou	intry of Manufacturer	To be mentioned	
6.	Cou	intry of Assembly	To be mentioned	
7.	Yea	er of production	Not before the calendar year of contract	
8.	App	licability	Trk 3 Ton Isuzu-HTS11G & 11J, Toyota HZJ-71 & 79	
Part -	<u>-2</u>			
TECH	<u>INIC/</u>	AL SPECIFICATION		
9.	Fun	oction & Capability	Details to be mentioned	
10.		erall weight of battery PP container	To be mentioned	
11.	Bat	tery 12 Volt 65 AH	To be provided	
	a.	Voltage	12V	
	b.	Capacity`	65 AH (Min)	
	C.	No. of Plate	13 Plate	
	d.	Dimension	L= 258-260 mm	
			W=170-173 mm	
			H= 221-230 mm	
12.	After discharging the minimum specific gravity at 30°C of the electrolyte.		1.050-1.100	
13.	Dis	charge Rate	C/20	
14.	Cell Capacity		Minimum 2.1 Volts	
15.	Separators		To be mentioned	
16.	Cor	ntainer	White Plastic Container with carrying handle/rope and screen print instrument. Upper and lower level of electrolyte identification mark should be leveled on the body of the battory.	geral of Deca
		-	be leveled on the body of the battery B 9 of 12	DEP

B 9 of 12 FOR OFFICIAL USE ONLY

Ser	General Description	Technical Specification	Must be filled up by the Manufacturer
17.	Self discharge rate	3% ~ 4% per month	
18.	Warranty	Minimum 01(One) year from the date	
		of actual use (After filling the electrolyte).	
19.	Per Battery Electrolyte	To be mentioned	
	Capacity including container		
20.	Density of Electrolyte at	To be mentioned	
	20°C		
21.	Physical	Clear, colorless, odorless liquid	
	AppearanceofShulphuric		
	acid		
22.	Shulphuric acid		
	a. Purity	99.97%	
	b. Density at 20°C	1.84	
23.	DM water (PH value)	P ^H = 5-6	
24.	<u>Plate</u>		
	a. No of positive plate	To be mentioned	
	b. No of Negative	To be mentioned	
	Plate		

B 10 of 12 FOR OFFICIAL USE ONLY



ITEM NO. 6, TECHNICAL SPECIFICATION OF SECONDARY BATTERY 12 VOLT 65 AH 13 PLATE, QTY-50 NOS

Ser	Ge	eneral Description	Technical Specification	Must be filled up by the Manufacturer
Part -	1			
	Gen	eral Specification		
1.	Nomenclature		Secondary Battery 12 Volt 65 AH 13 Plate	
2.	Brai	nd & Model	(LUCAS, HAMKO, GENERAL, NAVANA, VOLVO, RANGS POWER, RIMSO and SAIF POWER). Specific Brand to be mentioned	
3.		ne of manufacturer	To be mentioned	
		complete address	<u> </u>	
4.		ntry of Origin	To be mentioned	
5.		intry of Manufacturer	To be mentioned	
6.	Cou	intry of Assembly	To be mentioned	
7.	Yea	r of production	Not before the calendar year of contract	
8.	App	licability	Toyota Coaster BB-21 RMR, Isuzu Trk 3 Ton HTS-11J	
Part -	<u>·2</u>		-	
<u>TECH</u>	<u>INIC/</u>	AL SPECIFICATION		
9.	Fun	ction & Capability	Details to be mentioned	
10.	Overall weight of battery with PP container		To be mentioned	
11.	Bat	tery 12 Volt 65 AH	To be provided	
	a.	Voltage	12V	
	b.	Capacity`	65 AH (Min)	
	C.	No. of Plate	13 Plate	
	d.	Dimension	L= 260 mm	
			W=173 mm	
			H= 225 mm	
12.	Afte	er discharging the	1.050-1.100	
	L	imum specific gravity		
		60°C of the electrolyte.		
13.	1	charge Rate	C/20	
14.	Cell Capacity		Minimum 2.1 Volts	
15.	Separators		To be mentioned	
16.	 	ntainer	White Plastic Container with carrying	
10.			handle/rope and screen print instrument. Upper and lower level of	
	1		electrolyte identification mark should	EVELOTO OF

B 11 of 12 FOR OFFICIAL USE ONLY

Ser	G	eneral Description	Technical Specification	Must be filled up by the Manufacturer
17.	Self	discharge rate	3% ~ 4% per month	
18.	War	ranty	Minimum 01(One) year from the date of actual use (After filling the electrolyte).	
19.		Battery Electrolyte acity including tainer	To be mentioned	
20.	Density of Electrolyte at 20°C		To be mentioned	
21.	Physical AppearanceofShulphuric acid		Clear, colorless, odorless liquid	
22.	Shulphuric acid			
	a.	Purity	99.97%	
	b.	Density at 20°C	1.84	
23.	DM	water (PH value)	P ^H = 5-6	
24.	<u>Plate</u>			
	a.	No of positive plate	To be mentioned	
	b.	No of Negative Plate	To be mentioned	

B 12 of 12 FOR OFFICIAL USE ONLY



ANNEX C TO DGDP TENDER NO 214.1531.24 DATED: 28 NOVEMBER 2024

TERMS AND CONDITION OF SECONDARY BATTERY VARIOUS SIZES FOR DIFFERENT VEH, QTY- 06/560 NOS

Ser	Terms and Conditions	Must be filled
No.		up by the Manufacturer
1.	Source of Supply: Local.	
2.	Brand: (LUCAS, HAMKO, GENERAL, NAVANA, VOLVO, RANGS	
	POWER, RIMSO AND SAIF POWER). If dealers those are enlisted with	
	DGDP participate to supply standardized Brand, authorization certificate	
	from manufacturer has to be submitted. Specific Brand to be mentioned.	
3.	Country of Origin: To be mentioned.	-
4.	Country of Manufacturer/Assembly: To be mentioned.	
5.	Authority Holding Sealed Particulars (AHSP): Chief Inspector (CI),	
	Inspectorate of Electronics & Instruments (IE&I), Dhaka Cantonment.	
6.	Inspecting Authority: Chief Inspector (CI) of Inspectorate of Electronics &	
7	Instruments (IE&I) or his authorized representative, Dhaka Cantonment	
7.	Place of Inspection. a. Stage Inspection(SI). Manufacturer Factory Premises. Name and	
	address of factory- To be mentioned.	
	b. <u>Joint Post-shipment Inspection (JPSI).</u> Central Ordnance Depot	
	(COD)/Central Mechanical Transport Depot (CMTD), Dhaka Cantonment.	
8.	Stage Inspection (SI)	
	a. Before production of bulk stores, manufacturers will submit lab test	
	report for all kinds of raw materials required for battery manufacturing and	
	will take approval of raw material from Inspectorate. They will arrange	
	stage inspection during production. The stage inspection will be carried out	
	at manufacturer factory premises. Inspection team will visit the production	
	line of the equipment. All necessary facilities needed for inspection to be	
	arranged by the supplier without extra cost. All types of	
	movements/transportation of the team within the country/concerned area	
	for the inspection are also to be arranged by the supplier at their cost.	
	b. Inspection will be carried out basing on the technical specification	
	which is specified in the contract. All parameters of contracted technical	
	specification will be checked one by one. Supplier/manufacturer will	
<u> </u> 	ensure the presence of experts and provide all necessary facilities to show	
	each parameter physically in factory and laboratory (Where applicable).c. Provide necessary secretarial support (typing and printing facilities)	
	to the stage inspection team to be arranged by the supplier.	
	d. Manufacturing plant of all battery are to be visited by the Stage	
	Inspection (SI) team in order to confirm the year (Not before the contracted	
	year) of production in the assembly line.	
	e. A Stage Inspection (SI) report will be prepared and will be signed by	
	the competent representative of Manufacturer Local agent and SI team.	
	f. 100% stores to be sealed and signed on the suitable place of Battery	
	by the representative of Inspector of Inspectorate of Electronics &	
	Instruments (IE&I) after finish production.	General of Defence

C 1 of 5 FOR OFFICIAL USE ONLY

stry of Dele

Ser	Terms and Conditions	Must be filled
No.		up by the
		Manufacturer
9.	Joint Post-Shipment Inspection (JPSI).	
	a. General. Joint Post Shipment Inspection (JPSI) will be carried	`
	out on receipt of stores by the consignee (COD/CMTD). Date of JPSI	
	(Visual and Lab Test) will be decided by Inspection and Technical	
	Development (ITD) Director after necessary coordination with IE&I,	
	Local agent, User Director (If required) and manufacturer. In this	
	connection the local agent/manufacturer will intimate the actual date of	
	arrival of stores to IE&I&ITDDte just after the commencement of	·
	shipment. Following Representative will be present and carried out JPSI:	
	(1) Representative of Inspectorate of Electronics & Instruments	
	(IE&I)	
	(2) Local agent	
	(3) Manufacturer's expert (If any).	
ļ	(4) Consignee.	
	The inspection will be conducted in following 2 phases duration of the	
	inspection will be fixed by the purchaser.	
	(1) Visual inspection.	
	(2) Laboratory Test	
	b. <u>Visual inspection.</u>	
	Visual inspection of 100% stores will be carried out at COD/CMTD	
	premises. During visual inspection following parameters will be checked:	
	(1) Brand & Model.	
	(2) Country of Origin and Manufacture. (3) Year of production.	
	(4) Part no/ Serial No.	
	(5) Any damage/ crack etc.	
	(6) Measurement and weight etc.	
	(7) Packing and marking as per contract.	
	(8) Quantity as per contract.	
	(9) All sign and marking.	
ļ	(10) Any other if deemed necessary by inspection team.	
	c. Inspection Conditions.	
İ	(1) All parameters of contracted technical specification will be	
	checked one by one.	
	(2) The supplier will provide necessary facilities, transport	
	support required to show the parameters during various test	
	(Visual and lab test) of the equipment's free of cost as per terms	
	of clause 12 (a) and 12 (b) of DP 35.	
Ì	(3) This inspectorate (IE&I) will issue final inspection Note	
	(I/Note) after being successful completion of inspection and	
	supply of all contracted stores as specified in the contract.	
	(4) If any item found defective and not in accordance with	
	contracted specification during Joint Post Shipment Inspection	
	(JPSI) the supplier/ manufacturer will replace as per DGDF	
	Instruction.	
	(5) JPSI report to be signed by rep of all concerned	General of Defe
	(Consignee, IE&I and supplier expert).	Note: See
		ISL A SE

	(O) After completion of leist Doct Chipmont increasing	
	 (6) After completion of Joint Post Shipment Inspection (JPSI), a jointInspection report will be prepared and signed by the representatives of allconcerned. (7) Inspection Note (I/Note) will be issued by IE&I on completion of the following: (a) Supply of all contracted store. (b)Successful completion of functional/Laboratorytest. 	
	d. Functional/Laboratory Test	
	Functional/Laboratory test of 01% total quantity (randomly selected) will be carried at IE&I facilities. The battery function/performance further test will be carried out in the Laboratory of IE&I as per the Technical Specification. Above percentage (%) may be increased if necessary basing on performance test result of battery. Supplier needs to provide necessary required battery during Lab test as deemed necessary by Chief Inspector (CI) of IE&I.	
10.	Packing & Marking: a. As per international standard trade packing and marking. The stores are to be securely packed for safe transit by Railway/Road. The packing will be done by supplier so that the stores will not be affected by rain and damp weather during transportation. Marking must be done clearly in English Language in each container/packages for easy identification of the stores. Container/boxes must be strong enough to bear or withstand the load of contained materials during transportation. b. Contract number, date, and name of the consignee must be stenciled on the front side of the PP container/wooden box. c. Final acceptance seal of IE&I (↑1009) must be stamped on the suitable place of the items by indelible ink.	
11.	Certificate Conditions. a. Authorization certificate (Original) in favour of manufacturer by the local agent to be submitted along with offer. b. Authorization certificate (Original) in favour of local agent by the Principal (If applicable) to be submitted along with Offer. c. The following certificate must be provided by the manufacturer and local agent with the offer: (1) Manufacturer certificate confirming country of origin. (2) Manufacturer certificate confirming country of manufacturer/ Assembly. (3) After sales service should be available with the local agent of the supplierandisto be provided as and when required for indefiniteperiod (Free of changeup to guarantee period and thereafter with payment) (Certificate by local agent). (4) The word "BD Army" to be sealed on the suitable place on the items byindelible ink. (5) Manufacturer certificate is to be providewith the offer mentioning. Theitem/itemsfound defective and not it accordance with the Specification will be replace free of cost.	

Ser	Terms and Conditions	Must be filled up by
No.		the Manufacturer
	(6) Manufacturer's certificate showing year of production to be submitted duringStage Inspection (SI) and manufacturer is alsoconfirmed that all materials/elements/components of the secondarybattery must be Brand New andEquipment manufactured not before the contracted calendar year. (7) Year of production certificate must be provided by the manufactureralong with the offer. (8) Updated Environmental Certificate from Department of Environment(DOE), Bangladesh must be provided by the Manufacturer along with the offer. (9) Updated Certificate from Accumulator Battery Manufacturers &Exporters Association of Bangladesh (ABMEAB) must be provided by the manufactureralong with	
	the offer. (10) Updated Acid license must be provided by the	
	manufacturer along withthe offer. (11) Updated Fire license must be provided by the	
40	manufacturer along with the offer.	
12.	Warranty/ Guarantee by Manufacturer, Principal (If applicable) and Local Agent	
	a. A warranty/Guarantee certificate to be provided for the	
	equipment's/items for a trouble free service of 12 months(The	
	warranty period will be start from the date of actual use).	
	b. If any defect/discrepancies arises during fitting in the	
	respective equipment's/stores within warranty/guarantee period after	
	receipt by consignee/user unit, that must be repair/ replaced (as	
	applicable) free of cost.	
	c. The firms supplying equipment's/items on warranty will identify	
	these by attaching a warranty label/ dies or stenciling this by	
	indelible (permanent) paints on the equipment/ items as shown below:	
	WARRANTY	
	(Warranty valid for 01 (one)year from the date of actual	
	use(From the dateofactual use)	
	Contract no and date:Date of	
	supply:	
	Supplier's name & address with phone no:	
	Manufacturer's name & address with phone no:	
	Warranty time: 01 (One) year from the date of actual use.	
	d. A Warranty/Guarantee will be provided by the local agent in	
13.	DPL-15 as above.	
13.	Severe punitive action will be taken (Incl black list) against supplier who fails to supply stores within delivery schedule of contract).	
14.	Inspection and Testing Facilities:	
'	The supplier shall pay all costs connected with the inspection and	
	will provide without extra charge, all materials, tools, instruments,	
	transport, labor, & assistance, etc of every kind which the inspector	
	may consider necessary for the inspection. Supplier shall also	
	provide and deliver free of charge at such place as the inspector	
	C 4 of 5	E DOND

Ser No.	Terms and Conditions	Must be filled up by the Manufacturer
	may direct, such materials as he may be required for test. Cost of any laboratory test shall be borne by the supplieras per terms of clause 12(a) and 12(b) of DP-35.	
15.	a.Original offer must be submitted in letter head pad of manufacturer signed andsealed at every pages. Name, designation, mobile No, Fax No. E-mail address, website and mailing address of signatory must be mentioned.	
	 b. Original brochure/catalogue of offered model with proper marking and signedmust be submitted along with the offer. 	
	c. Offered technical specifications must be conformed to the specificationsmentionedin the submitted brochure/catalogue. Fax/photocopy/hand written offer/catalogue/brochure and catalogue without marking/signing will not be considered during technical vetting.	
	d. Hand written offer and any hand written clarification will be directly rejected. Itmust be typed or computer printout in original letter head pad of the manufacturer/principal/local agent (As applicable) with sign and seal of proper signing authority.	
	e. Tempered offer will be directly rejected. f. The format must be filled up without changing any word/serial as	
	given in Tender Documents. g. Any offer may be accepted/rejected without asking any clarification.	
	h. A soft copy of the offer to be submitted in CD in Microsoft word documents for IE&I. However, hard copy is the final authority for offer vetting.	
16.	01x Complete Tender Sample (Each item)must be submitted along with the offer for functional test.	
17.	01x Complete Advance Sample (Each item) must be submitted after signing the contract and approved by the IE&Ibefore Bulk production.	
18.	Bulk Representative (BR) Sample must be submitted for functional test in accordance to approved advance sample. Quantity of BR Sample as mentioned in serial 9d.	
19.	Accept/reject will be confirmed according to submitted offer.	
20.	All kinds of raw materials for the production of Battery Various Sizes For Different Vehstorage in a bond room of factories premises and inspected by the authorized representative of IE&I.	
21.	All test and trail will be carried out in the factory premises Lab, which is not possible by IE&I Lab due to non-availability of test equipment.	
22.	Rejected items must be replaced free of cost at the supplier's expense.	
23.	No deviation from the contracted specification after signing the contract will be acceptable during stage inspection.	
24.	Any defect/ damage/ pilferage or discrepancies arise during transportation will be repaired/ fulfilled by the manufacturer.	

C 5 of 5 FOR OFFICIAL USE ONLY

