TECHNICAL SPECIFICATION OF ITEM NO 1, H-1(C)-HA-13550, GREASE PX-11 (PRESERVATIVE MINERAL JELLY BEES WAX)

Ref:

- A. BOF Specification no SYB-1501-56 for Rifle Grease.
- B. Standard Handbook for Mechanical Engineers.
- C. Fuchs Product Information Brochure for 'Renolit FEP' Product code 503.
- D. Mobil Product Guide 'Mobilux EP.
- E. Meghna Petroleum Ltd. Brochure for 'BP Anergrease LS and LSEP.
- F. Shell Lubricants Handbook.
- 01. <u>Composition</u>: 9 Parts of PX-6 and 1 Part of Bees wax (100% pure)
- 02. <u>Characteristics of PX-11:</u>

a. Base Lithium

b. Penetration worked at 25°C 265~ 295

c. Reaction Neutral or alkalescent.

d. Corrosion test (Steel specimen, 100° C, 3 hours No corrosion should appear.

e. Ash Content 0.05 % (Max)

f. Acidity 0.35 mg KOH/gm (Max)

g. Dropping Point ${}^{\circ}$ C 180 ~ 190

03. Other Terms and Conditions

- a. Before preparation of Grease PX-11, its main constituents/ingredients i.e PX-6 and Bees wax must be submitted separately to IA&E for inspection and approval. The accepted ingredients will be mixed in presence of IA&E representative for preparation of Grease PX -11.
- b. The grease should be procured from any authorized manufacturer of Bangladesh Petroleum Corporation and should ensure the following points.
 - Container used in packing should be new, cleaned and sealed.
 - (2) Quality Certificate from the manufacturer with the results conforming the specified quality of their standard products should be submitted.
 - (3) Warranty/Guarantee certificate should be submitted to the effect that the store will not deteriorate during use at least for 01 (one) year.
 - (4) Description of the store with nomenclature, date of production and name of manufacture should be printed on each container.
- c. Authority Holding Sealed Particulars :CI, IA&E Gazipur Cantt.

d. Inspecting Officer : CI,IA&E or his authorized representative

e. Inspection Instruction : Before bulk supply the account sample must be approved by A&E

A-1 RESTRICTED

1124 121