### FOR OFFICIAL USE ONLY

Directorate General Defence Purchase Ministry of Defence New Airport Road Tejgaon Dhaka-1215

Tel: 5040 (Army) 48116909 (BTCL) E-Mail: adp2army1@dgdp.gov.bd

Agrahayan 1431

06.06.0000.215.49.24/Re-Eval

26 November 2024

# BOFO- PROCUREMENT OF MAN PORTABLE HIGH POWER ELECTRONIC COUNTERMEASURE (CELL/GPS/JAMMER)

Reference:

A. Army Headquarters, Engineer in Chief's Branch, Engineer Directorate letter number 23.01.901.055.02. 192.01.21.10.24 dated 21 November 2024 (Not to all).

In light of above reference, the technical specification of **Man Portable High Power Electronic Countermeasure (Cell/GPS/Jammer)** is attached with this letter. Interested local firms/agents are requested to send necessary offers, catalogues, brochures, technical/training/operational/maintenance manuals and budgerary offers etcetera directly to Army Headquarters, Engineer in Chief's Branch, Engineer Directorate with intimation to this office by **08 December 2024.** 

MD ZAHIDUL KABIR Major For Director General

#### Enclosure:

1. Technical Specification-04 (Four) Pages Only.

Distribution:

External:

Information:

Army Headquarters

General Staff Branch, Weapon Equipment & Statistics Directorate

Army Headquarters, Engineer in Chief's Branch, Engineer Directorate

Army Headquarters
Master General of the Ordnance Branch
Ordnance Directorate

Army Headquarters
Master General of the Ordnance Branch
Inspection and Technical Development Directorate

Inspectorate of Electronics & Instruments Dhaka Cantonment

Action:

All Concerned Supplier/Firm

Internal:

IT Section (For uploading to website)

FOR OFFICIAL USE ONLY

# <u>Technical Specification of Man Portable High Power Electronic Countermeasure</u> (Cell/GPS/Jammer)

Ser	Description	Required Technical Specification	Must be filled up by Principal/ Manufacturer
(a)	(b)	(c)	(e)
Part-	1: General Specification		
1.	Name of the Equipment	Man Portable High Power Electronic Countermeasure (Cell/ GPS/ Jammer)	
2.	Brand	To be mentioned	
3.	Model	To be mentioned	
4.	Year of Production	Brand new and not before the contracted year	
5.	Country of origin	Group A & B Countries	
6.	Country of Manufacturer/ Assembly	Group A & B Countries	
7.	Name of Manufacturer with complete address (Office address, Telephone, Fax, E-Mail and web address	Details to be mentioned	
8.	Name of Principal with complete address (Office address, Telephone, Fax, E-Mail and web address	Details to be mentioned	
9.	Name of Local Agent with complete address (Office address, Telephone, Fax, E-Mail and web address	Details to be mentioned	
10.	General Description, Functions and capabilities	a. It should be able to block/Jam all types of device simultaneously within the frequency band as specified in technical specification     b. It should be capable of performing active and	
		reactive or hybrid jamming to a target.  c. Relatively small and backpack mounted d. Should support one/several open communication window on each band for own communication e. The Jammer should be in active service of different militaries/Law enforcement agencies. List to be mentioned.	
Part-	2: Technical Specification		
11.	Type of Jamming	<ul> <li>a. The systems should not be restricted to a single method of jamming, rather it should integrate multiple, varying methods into a single system.</li> <li>b. It should have both barrage, spot jamming</li> </ul>	
		capability. Details to be mentioned.	
12.	System design	<ul> <li>a. DDS (Different Digital Synthesis) to be used to generate jamming output.</li> <li>b. On board DDS based FPGA controlled technology to be used.</li> </ul>	
13.	Operational Jamming Radius	360°	
14.	Operational Jamming Range (m)	Jamming range of singled jammer is as follows: <u>Urban Area</u> . Minimum 40 meters radius. <u>Open Area</u> . Minimum 60 meters radius.  Testing procedure of Jammer is attached as appendix 1.	
15.	Operation Frequency Range	<ul> <li>a. The system should cover the entire frequency range from 20MHz to 2500 MHz for jamming.</li> <li>b. The system must be configured/programmed by the end user at any frequency within frequency band down to 1KHz resolution.</li> </ul>	
16.	Operation Frequency Band	Minimum 03 band should be available.	
17.	Available Jamming Standard	<ul> <li>a. VHF, UHF, Wi-Fi, Bluetooth, GSM (2G, 3G, 4G) to be mentioned. Other Jamming standards may also be mentioned (if available).</li> <li>b. Must be able to jam multiple threats simultaneously in real time.</li> <li>c. Maximum simultaneous jamming bandwidth to mentioned.</li> </ul>	

## RESTRICTED

18. Continuous Uninterruptable Jamming Period  Power output (W)  19. Power output (W)  20. Initial Warm up time  20. Initial Warm up time  21. Power Consumption  22. Battery  22. Battery  23. Type of Battery  24. C. Low Battery Alarm  25. Low Battery Operating Time  26. D. Battery Operating Time  27. D. Battery Operating Time  28. Continuous Uninterruptable Jam of be mentioned.  29. D. Battery Operating Time  20. D. Battery Operating Time  20. D. Battery Operating Time  21. D. Battery Operating Time  22. D. Battery Operating Time  23. A Power Source:  AC Power and Charging facility  BC Power Source  AC Power so	
above in case of GSM, UMTS and LTE signals. b. The power output to given for each band as follows:  Band Frequency Watt  VHF  UHF  2G  3G  4G  Wi-Fi  Bluetooth  20. Initial Warm up time The system's minimum time required before operation from cold-start shall not exceed 01 (One) minutes.  21. Power Consumption  a. At Maximum RF Power To be mentioned. b. At Stand By Mode To be mentioned.  22. Battery  a. Type of Battery  a. Rechargeable Lithium-lon/lithium-polymer or equivalent. b. One additional battery to be provided.  Minimum 2 Hours continuous operation for any band. c. Low Battery Alarm The System should have audio/visual indication for low battery warning.  d. Operational Power Source:  AC Power and Charging facility be provided.  DC power source  AC Power and Charging facility be provided.  DC power source  System to be operated from DC power source. Power source will be replaceable and rechargeable. e. Battery charging time with battery charger  Antenna a. Type b. Number of Antennas To be mentioned (Minimum 2, Must cover full	
VHF UHF 2G 3G 4G Wi-Fi Bluetooth  The system's minimum time required before operation from cold-start shall not exceed 01 (One) minutes.  21. Power Consumption a. At Maximum RF Power b. At Stand By Mode To be mentioned. b. At Stand By Mode To be mentioned. b. Battery a. Type of Battery  a. Rechargeable Lithium-lon/lithium-polymer or equivalent. b. One additional battery to be provided. b. Battery Operating Time Minimum 2 Hours continuous operation for any band. c. Low Battery Alarm The System should have audio/visual indication for low battery warning. d. Operational Power Source: AC Power and Charging facility DC power source AC Power source AC 220 ± 10%, 50Hz, Standard power source will be provided. System to be operated from DC power source. Power source will be replaceable and rechargeable. e. Battery charging time with battery charger Antenna a. Type High Gain Omni directional Antennas. To be mentioned (Minimum 2, Must cover full	
VHF UHF 2G 3G 4G Wi-Fi Bluetooth The system's minimum time required before operation from cold-start shall not exceed 01 (One) minutes.  21. Power Consumption a. At Maximum RF Power b. At Stand By Mode To be mentioned.  22. Battery a. Type of Battery a. Type of Battery  b. Battery Operating Time C. Low Battery Alarm C. Low Battery Alarm C. Depretional Power Source: AC Power and Charging facility DC power source  Battery Carbon Ac 220 ± 10%, 50Hz, Standard power source will be provided.  Bystem to be operated from DC power source. Power source will be replaceable and rechargeable.  E. Battery charging time with battery charger  Antenna a. Type B. Number of Antennas To be mentioned (Minimum 2, Must cover full)	
2G 3G 4G Wi-Fi Bluetooth  Initial Warm up time The system's minimum time required before operation from cold-start shall not exceed 01 (One) minutes.  21. Power Consumption a. At Maximum RF Power b. At Stand By Mode To be mentioned.  22. Battery a. Type of Battery  a. Type of Battery  a. Rechargeable Lithium-lon/lithium-polymer or equivalent. b. One additional battery to be provided.  b. Battery Operating Time Minimum 2 Hours continuous operation for any band.  c. Low Battery Alarm The System should have audio/visual indication for low battery warning.  d. Operational Power Source: AC Power and Charging facility DC power source System to be operated from DC power source will be provided.  DC power source will be replaceable and rechargeable. e. Battery charging time with battery charger  Antenna a. Type High Gain Omni directional Antennas. To be mentioned (Minimum 2, Must cover full	
3G   4G   Wi-Fi   Bluetooth	
AG   Wi-Fi   Bluetooth   The system's minimum time required before operation from cold-start shall not exceed 01 (One) minutes.    Power Consumption   a. At Maximum RF Power   b. At Stand By Mode   To be mentioned.	
Wi-Fi   Bluetooth	
Bluetooth   The system's minimum time required before operation from cold-start shall not exceed 01 (One) minutes.    Power Consumption	
Initial Warm up time	
21. Power Consumption  a. At Maximum RF Power	
b. At Stand By Mode  Battery  a. Type of Battery  a. Type of Battery  a. Rechargeable Lithium-lon/lithium-polymer or equivalent. b. One additional battery to be provided.  b. Battery Operating Time  Minimum 2 Hours continuous operation for any band.  c. Low Battery Alarm  The System should have audio/visual indication for low battery warning.  d. Operational Power Source:  AC Power and Charging facility  DC power source  System to be operated from DC power source.  Power source will be replaceable and rechargeable.  e. Battery charging time with battery charger  23. Antenna  a. Type  High Gain Omni directional Antennas.  To be mentioned (Minimum 2, Must cover full)	
22. Battery  a. Type of Battery  a. Rechargeable Lithium-lon/lithium-polymer or equivalent. b. One additional battery to be provided.  b. Battery Operating Time  Minimum 2 Hours continuous operation for any band.  c. Low Battery Alarm  The System should have audio/visual indication for low battery warning.  d. Operational Power Source:  AC Power and Charging facility  DC power source  System to be operated from DC power source. Power source will be replaceable and rechargeable.  e. Battery charging time with battery charger  23. Antenna  a. Type  High Gain Omni directional Antennas.  To be mentioned (Minimum 2, Must cover full)	
a. Type of Battery  a. Rechargeable Lithium-lon/lithium-polymer or equivalent. b. One additional battery to be provided.  b. Battery Operating Time  Minimum 2 Hours continuous operation for any band.  c. Low Battery Alarm  The System should have audio/visual indication for low battery warning.  d. Operational Power Source:  AC Power and Charging facility  DC power source  System to be operated from DC power source.  Power source will be replaceable and rechargeable.  e. Battery charging time with battery charger  23.  Antenna  a. Type  High Gain Omni directional Antennas.  To be mentioned (Minimum 2, Must cover full	
equivalent. b. One additional battery to be provided.  b. Battery Operating Time  C. Low Battery Alarm  C. Low Battery Alarm  The System should have audio/visual indication for low battery warning.  d. Operational Power Source:  AC Power and Charging facility  DC power source  System to be operated from DC power source.  Power source will be replaceable and rechargeable.  e. Battery charging time with battery charger  Antenna  a. Type  High Gain Omni directional Antennas.  To be mentioned (Minimum 2, Must cover full	
b. Battery Operating Time  C. Low Battery Alarm  C. Low Battery Alarm  The System should have audio/visual indication for low battery warning.  d. Operational Power Source:  AC Power and Charging facility  DC power source  System to be operated from DC power source.  Power source will be replaceable and rechargeable.  E. Battery charging time with battery charger  Antenna  a. Type  High Gain Omni directional Antennas.  To be mentioned (Minimum 2, Must cover full)	
for low battery warning.  d. Operational Power Source:  AC Power and Charging facility  DC power source  e. Battery charging time with battery charger  AC 220 ± 10%, 50Hz, Standard power source will be provided.  System to be operated from DC power source.  Power source will be replaceable and rechargeable.  To be mentioned.  Antenna  a. Type  High Gain Omni directional Antennas.  b. Number of Antennas  To be mentioned (Minimum 2, Must cover full	
AC Power and Charging facility  DC power source  E. Battery charging with battery charger  23.  Antenna  a. Type  B. Number of Antennas  AC 220 ± 10%, 50Hz, Standard power source will be provided.  System to be operated from DC power source.  Power source will be replaceable and rechargeable.  To be mentioned.  High Gain Omni directional Antennas.  To be mentioned (Minimum 2, Must cover full)	
facility  DC power source  System to be operated from DC power source. Power source will be replaceable and rechargeable.  e. Battery charging time with battery charger  23.  Antenna  a. Type  B. Number of Antennas  High Gain Omni directional Antennas. To be mentioned (Minimum 2, Must cover full)	
DC power source  System to be operated from DC power source. Power source will be replaceable and rechargeable.  e. Battery charging time with battery charger  23.  Antenna  a. Type  B. Number of Antennas  High Gain Omni directional Antennas. To be mentioned (Minimum 2, Must cover full	
Power source will be replaceable and rechargeable.  e. Battery charging time with battery charger  23.  Antenna a. Type b. Number of Antennas  High Gain Omni directional Antennas. To be mentioned (Minimum 2, Must cover full	
with battery charger  23. Antenna a. Type High Gain Omni directional Antennas. b. Number of Antennas To be mentioned (Minimum 2, Must cover full	
23. Antenna a. Type High Gain Omni directional Antennas. b. Number of Antennas To be mentioned (Minimum 2, Must cover full	
b. Number of Antennas To be mentioned (Minimum 2, Must cover full	
The property of the property o	
c. Antenna Impedance ( $\Omega$ ) To be mentioned	
d. Antenna Height Antenna along with the jammer should not exceed 1.5m.	
e. Antenna sensitivity	
24. Cooling System To be mentioned.	
25. Dimension of Jammer Set (Lx Hx W) To be mentioned.	
26. Weight (In full Operational condition)  To be mentioned. It should be less than 20 Kg.	
27. Colour To be mentioned 28. Environmental Standards	
a. Operational Temperature  O°C to +60°C	
b. Humidity 95% Humidity or above	
c. Vibration To be mentioned.	
d. Rain/Splash Proof  To be mentioned.	
f. Protection against a. RF & EMI Shielding protective layers to avoid Radiation and EMI RF/EMI interferences.	
Shielding  b. The equipment must be designed to protect user from Radiation hazard of any protective suit needs to be worn should be included in list of standard item.	
c. Certificate to be provided by the manufacturer regarding health hazard.	
g. Storage Temperature To be mentioned	
29 Built in Diagnostic Self- Test/Alarm System	
a. VSWR To be mentioned.	
b. Low & Over Voltage. To be mentioned. c. Over Temperature To be mentioned.	
d. Additional features to be To be mentioned.	
mentioned	

## RESTRICTED

Ser	Description		Required	echnicai Sp	ecification			t be filled up by cipal/ Manufacturer
30.	Connectivity		a. Jammer	should have	provision of va	arious ports		
					tc) for conne			
					ptops/ Moder	n etc for		
			software into		of wined/wine			
					n of wired/wirel te the jamm			
			distance	to opera	te the janin	er nom a		
31.	Backpack C	arrier	To be menti	ioned.				
32.	Maximum O		Minimum 25					
	Altitude		77 San 201 A 10211 1 1 1					
33.	GPS Facility	(In Built)		lable (Details To be mentioned)				
34.	Control soft	ontrol software a. Easily Programmable Software to be installed						
	in Windows 10 or later version operating system. b. Control and programming backup software to							
				with the sys		Software to		
					ftware to be pi	rovided with		
			the tender of	document.				
35.	Laptop (4:1) Internationally reputed brand laptop should be included in the system Origin from Group A & Manufactured/Assembly from Group B countries.							
				red/Assemb	ly from Group	B countries.		
	Detail config	urations are as u	nder:	oration or ab	oue Minimum	2.2.047		
	a. Processo	or: Core i7 or abo	ve, iith gene	eration of ab	ove, wiminum	2.2 5112		
		nimum 500GB or	higher (prefe	erably SSD)				
		GB DDR3 RAM o						
	d. Motherbo	oard: To be menti	oned.					
		Minimum 12 inch						
		information- Det						
36.	Maintenanc	e support			be provide t			
					for 05 (Five) year			
					waveform sup			
					or 05 (Five) year			
37.	Model Valid	ity	Minimum 10 years. Certificate to be provided by					
			the manufacturer					
38.	Any other  Any items/accessories not mentioned above but require for full range of operation/use of the					1		
					or operation/			
39.	List of stand	lard		e mentioned		onea.		
00.		accessories (For full range						
-	of operation	)						~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
	Bil of Quantity/Material (BOQ/BOM) of Standard items							
							••	
	Ser	Name of item	Brand		Model	Quant	ity	Country of Manufacturer
	1.							Manufacturer
	1.	L			L			
40.	List of Option	nal	Details to b	e mentioned	1			
	accessories							
		Bil of	Quantity/Ma	aterial (BOC	(/BOM) of Opti	onal items		
								Country of
	Ser	Name of item	Brand		Model	Quan	ity	Country of Manufacturer
	1.				<u> </u>		·/·	Manadatate
	2.				1			
Part		REQUIREMENT	[					
41.	a. User	Tra	To be provi	ided (As ner	requirement of	Engr Dte)	T	
T 11		epair and maint	To be provi	ided (As per	requirement of	EME Dte)	<del>                                     </del>	
	Trg							
	c. Eqpt mgt Trg To be provide			requirement of				
Part	-4: REPAIR A	ND MAINTENAN	ICE REQUIR	REMENT LE	SS LIST OF S	PARES		
42.	a. Books &	a. Books & Publications						
	(1) Owners/Operations Manual in			ided (As per re	quirement			
	English (Book Type including CD/DVD)		of EME Dte					
	(2) 100% Updated Master Spare Parts			ided (As per re	quirement			
	Catalogue in English (Book Type		of EME Dte	∍)				
	including C		loots -	Tobo	idad (Aa sas ==	auiromant	-	
		te and Updated M		of EME Dte	ided (As per re	quirernent		
	Spare Parts price Catalogue in English (Book Type including CD/DVD)		OI LIVIE DR	-1				
	(4) Worksh	op/Repair Manua	l in English	To be provided (As per requirement				
	(Book Type		g.,	of EME Dte		,		
	1							

## RESTRICTED

Ser	Description	Required Technical Specification	Must be filled up by Principal/ Manufacturer
Part-	5:LIST OF SPARES		
43.	List of Fast and Slow Moving Spare Parts	To be provided (As per requirement of EME Dte)	
Part-	6:TOOL LIST FOR DIFFERENT LEVEL C	F MAINTENANCE	
44.	a. Analyzer, measuring & testing/Fault finding and diagnostic set	To be provided (As per requirement of EME Dte)	
	b. Special Service Tools (SST)	To be provided (As per requirement of EME Dte)	
	c. Special Service Materials (SSM)	To be provided (As per requirement of EME Dte)	